100% VIRGIN MATERIAL CER1

MELOS® CUSHION+

The cushioning and base layer for fall protection surfaces with 100 % virgin material.

Melos[®] Cushion⁺ is a high-quality system component for the base layer in athletics and multi-sport surfaces. The special feature: Melos[®] Cushion⁺ consists of 100 % EPDM virgin material! Due to the fibrous material form, the best fall protection properties are achieved – and this with an optimized material consumption. Melos[®] Cushion⁺ is manufactured from high-quality raw materials, is 100 % REACH-compliant* and is highly water-permeable for ideal durability. All requirements for contemporary fall protection are met. Rely on product features that pay off for clients, give parents a safe feeling and are simply fun for children.



Consistent Safety

Weatherproof

me



Sustainable and economical



Sensible use of resources in the long term

Flame-retardant**

Eco-friendly

Barrier-free



» Product information

Property	Unit	Value ¹	Test standards
Density	g/cm ³	60	DIN EN ISO 1183-1
Bulk density (±10%)	g/l	320	DIN EN ISO 1097-3
Hardness	Shore A	60	DIN ISO 48-4
Tensile strength	MPa	> 3	DIN 53504
Elongation at break	%	> 700	DIN 53504
Grain size	mm	2.0 – 30.0 (shares > 30.0 mm possible depending on process)	
Polymer base	EPDM		
Flame retardance	Flame-retardant material compliant with class $\rm C_{ff}{-}s1$ (DIN EN 13501-1) on request		

» Environmental and health tests

EN 71-3	Fulfils the requirements of the toy safety standard with respect to the migration of certa components.	ain
PAH (REAC	 Fulfils the requirements of the REACH regulati (EG) No. 1272/2013, appendix XVII, entry 28 and 50. 	on

¹ Technically related variations in property, colour and production-related variations as well as innovations and technical changes are reserved. Products shown may differ in configuration from the actual product.

* REACH-Regulation Annex XVII, Entry 28 and 50

** On request



Melos GmbH Bismarckstrasse 4-10 49324 Melle, Germany Tel.: +49 (0)54 22 94 47-0 Fax: +49 (0)54 22 59 81 Email: info@melos-gmbh.com Follow us on social media:

0



www.melos-gmbh.com

2